

COMPARE OUR BIFOLD SYSTEMS

	ALUMINIUM	TIMBER	UPVC
Standard White	Y	Y	Y
RAL Colours	Y	Y	N
Dual Colours	Y	N	Y
Textured Colours	Y	N	N
Woodgrain Foils	N	N	Y
Translucent Stains	N	Y	N
Concealed Trickle Vents	Y	N	Y
Weathered Threshold	50mm	52mm	52mm
Flush Threshold	20mm	7mm	7mm
Ramp Threshold	Y	N	N
High Security Locking	Y	Y	Y
Concealed Hinge Fixing	Y	Y	Y
Concealed Rollers	Y	Y	Y
Intermediate Locking Handles	Y	Y	Y
D Handles	Y	Y	Y
Overall U-values w/2mk*	1.5	1.4	1.7
Maximum Width**	6200mm	6200mm	4700mm
Maximum Height	2500mm	2500mm	2200mm
Maximum Panel Width	1000mm	1000mm	750mm
Glass to glass sight lines***	132mm	138mm	132mm

*Using our standard 1.0 U-value Staycool solar control double glazing.

**Wider doors are possible in aluminium and timber – please call for details.

***Sightlines based on width of aluminium, timber or upvc between each glass unit on panels folding sliding in the same direction. Additional meeting stiles will be necessary where traffic doors are hinged in the opposite direction to the main stack which will increase the sightlines.